

# Material Safety Data Sheet



## SCAT 2 CYCLE 50:1 OIL

### 1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

SCAT 2 Cycle Engine Oil

Conoco MSDS Code: MOTC0207

Revised: 13-February-2002

"SCAT" is a trademark of Conoco.

Product Use: 2-Cycle Oil

#### MANUFACTURER/DISTRIBUTOR

Conoco Inc.  
P.O. Box 2197  
Houston, TX 77252

#### PHONE NUMBERS

Product Information: 1-281-293-5550  
Transport Emergency: CHEMTREC 1-800-424-9300 (U.S. & Canada)  
1-703-527-3887 (international; call collect)  
Medical Emergency: 1-800-342-5119 or 1-281-293-5119

WEB SITE: [www.conoco.com](http://www.conoco.com)

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	%
Highly refined base oils	>70
Proprietary additives	<30

If oil mist is generated, exposure limits apply (see Section 8).

### 3. HAZARDS IDENTIFICATION

#### --- EMERGENCY OVERVIEW ---

#### APPEARANCE / ODOR

Red liquid / hydrocarbon odor.

#### OSHA REGULATORY STATUS

This material is classified as hazardous under OSHA Regulations.

#### COMBUSTIBLE

ASPIRATION INTO THE LUNGS MAY CAUSE LUNG DAMAGE OR DEATH.

HMIS RATING Health: 1; Flammability: 2; Reactivity: 0.

NFPA RATING Health: 0; Flammability: 2; Instability: 0.

#### Potential Health Effects

Primary Route of Entry: Skin

The product, as with many petroleum products, may cause minor skin, eye, and lung irritation, but good hygienic practices can minimize these effects.

Extreme overexposure or aspiration into the lungs may cause lung damage or death.

Normal use of this product does not result in generation of an oil mist. However if an oil mist is generated, overexposure can cause minor and reversible irritation to the eyes, skin, and especially the lungs. Proper personal protective equipment and sufficient ventilation can provide adequate protection.

#### Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

---

#### 4. FIRST AID MEASURES

---

##### Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

##### Skin Contact

Wash skin thoroughly with soap and water. If irritation develops and persists, consult a physician.

##### Eye Contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

##### Ingestion

Material poses an aspiration hazard. If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration.

##### Notes to Physicians

Activated charcoal mixture may be administered. To prepare activated charcoal mixture, suspend 50 grams activated charcoal in 400 mL water and mix thoroughly. Administer 5 mL/kg, or 350 mL for an average adult.

---

#### 5. FIRE FIGHTING MEASURES

---

##### Flammable Properties

Flash Point	: 93 C (199 F) (Minimum)
	95 C (203 F) (Typical)
Method	: Pensky-Martens Closed Cup - PMCC.
Flammable limits in Air, % by Volume	
LEL	: Undetermined
UEL	: Undetermined
Autoignition	: Undetermined

##### Extinguishing Media

Water Spray, Foam, Dry Chemical, CO2.

#### Fire Fighting Instructions

Use water to keep fire-exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for personnel attempting to stop a leak. Water may be used to flush spills away from exposures.

Products of combustion may contain carbon monoxide, carbon dioxide, and other toxic materials. Do not enter enclosed or confined space without proper protective equipment including respiratory protection.

---

### 6. ACCIDENTAL RELEASE MEASURES

---

#### Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Remove source of heat, sparks, and flame.

#### Initial Containment

Dike spill. Prevent material from entering sewers, waterways, or low areas.

#### Spill Clean Up

Recover free liquid for reuse or reclamation. Soak up with sawdust, sand, oil dry or other absorbent material.

---

### 7. HANDLING AND STORAGE

---

#### Handling (Personnel)

Avoid breathing vapors or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Wash contaminated clothing prior to reuse.

#### Handling (Physical Aspects)

Close container after each use. Do not pressurize, cut, weld, braze, solder, grind, or drill on or near full or empty container. Empty container retains residue (liquid and/or vapor) and may explode in heat of a fire.

#### Storage

Store in accordance with National Fire Protection Association recommendations. Store in a cool, dry, well-ventilated place. Store below 150 F (66 C). Store away from oxidizers, heat, sparks and flames.

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

#### Engineering Controls

##### VENTILATION

Normal shop ventilation.

#### Personal Protective Equipment

##### RESPIRATORY PROTECTION

None normally required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Select appropriate NIOSH-approved respiratory protective equipment when exposed to sprays

or mists. Proper respirator selection should be determined by adequately trained personnel and based on the contaminant(s), the degree of potential exposure, and published respirator protection factors.

#### PROTECTIVE GLOVES

Should be worn when the potential exists for prolonged or repeated skin contact. NBR or neoprene recommended.

#### EYE PROTECTION

Safety glasses with side shields; chemical splash goggles if splashing is probable.

#### OTHER PROTECTIVE EQUIPMENT

Coveralls with long sleeves if splashing is probable.

#### Applicable Exposure Limits

If oil mist is generated, exposure limits apply.

PEL (OSHA)	: 5 mg/m <sup>3</sup> , 8 Hr. TWA
TLV (ACGIH)	: 5 mg/m <sup>3</sup> , 8 Hr. TWA, STEL 10 mg/m <sup>3</sup>

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

---

#### Physical Data

Boiling Point	: Not Available
Vapor Pressure	: Negligible @ 60 F (16 C)
Vapor Density	: >1 (Air=1.0)
% Volatiles	: Nil
Evaporation Rate	: Nil
Solubility in Water	: Nil
Odor	: Hydrocarbon.
Form	: Liquid.
Color	: Red.
Specific Gravity	: 0.87 @ 60 F (16 C)
Density	: 7.27 lb/gal @ 60 F (16 C)

---

### 10. STABILITY AND REACTIVITY

---

#### Chemical Stability

Stable at normal temperatures and storage conditions.

#### Conditions to Avoid

Heat, sparks, and flames.

#### Incompatibility with Other Materials

Incompatible or can react with strong oxidizers.

#### Decomposition

Normal combustion forms carbon dioxide; incomplete combustion may produce carbon monoxide.

#### Polymerization

Polymerization will not occur.

---

### 11. TOXICOLOGICAL INFORMATION

---

#### Animal Data

Mouse skin painting studies have shown that highly solvent-refined petroleum distillates similar to ingredients in this product have not

caused skin tumors.

---

12. ECOLOGICAL INFORMATION

---

Ecotoxicological Information

No specific aquatic data available for this product.

---

13. DISPOSAL CONSIDERATIONS

---

Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations. Do not flush to surface water or sanitary sewer system.

Container Disposal

Empty drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All other containers should be disposed of in an environmentally safe manner.

---

# 14. TRANSPORTATION INFORMATION

---

Shipping Information

DOT:

Highway/Rail (Bulk): Petroleum products, n.o.s., 3, UN1268, III.  
Highway/Rail (Non-Bulk): Not Regulated

Quantity Limitations, Passenger Aircraft: 60L  
Quantity Limitations, Cargo Aircraft : 220L

---

15. REGULATORY INFORMATION

---

U.S. Federal Regulations

OSHA HAZARD DETERMINATION

This material is hazardous as defined by OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA/SUPERFUND

Not applicable; this material is covered by the CERCLA petroleum exclusion.

SARA, TITLE III, 302/304

Extremely Hazardous Substance: None

SARA, TITLE III, 311/312

Acute : Yes  
Chronic : No  
Fire : Yes  
Reactivity : No  
Pressure : No

SARA, TITLE III, 313

Toxic Chemical: None

TSCA

Material and/or components are listed in the TSCA Inventory of Chemical Substances (40 CFR 710).

RCRA

This material has been evaluated for RCRA characteristics and does

not meet hazardous waste criteria if discarded in its purchased form. Because of product use, transformation, mixing, processing, etc., which may render the resulting material hazardous, it is the product user's responsibility to determine at the time of disposal whether the material meets RCRA hazardous waste criteria.

CLEAN WATER ACT

The material contains the following ingredient(s) which is considered hazardous if spilled into navigable waters and therefore reportable to the National Response Center (1-800-424-8802).

Ingredient : Petroleum Hydrocarbons.  
Reportable Quantity : Film or sheen upon or discoloration of any water surface.

State Regulations (U.S.)

CALIFORNIA "PROP 65"

Ingredients subject to Act - None

PENNSYLVANIA WORKER & COMMUNITY RIGHT TO KNOW ACT

Ingredients subject to Act - None

Canadian Regulations

This is a WHMIS Controlled Product.

WHMIS Class: B3 - Combustible Liquid

-----  
16. OTHER INFORMATION  
-----

Additional Information: None.

-----  
The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS : MSDS Coordinator  
Address : Conoco Inc.  
> : PO Box 2197  
> : Houston, TX 77252  
Telephone : 1-281-293-5550

# Indicates updated section.

End of MSDS