

Page: 1 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

1. PRODUCT AND COMPANY IDENTIFICATION

MSDS No.: 01922190

SUPPLIER: Prepared by Product Safety: (800) 248-2481
Dow Corning Corporation NEWALTA: (800) 567-7455
South Saginaw Road Revision Date: 2011/01/04

Midland, Michigan 48686

MANUFACTURER: 24 Hour Emergency Telephone: (989) 496-5900

Dow Corning Corporation South Saginaw Road Midland, Michigan 48686

WHMIS CLASSIFICATION: Class D, Division 2, Subdivision A.

Material Usage: Sealant and adhesive

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Generic Description: Silicone elastomer

Physical Form: Paste
Colour: White
Odour: Not available

POTENTIAL HEALTH EFFECTS

Acute Effects

Eye: Direct contact may cause temporary redness and discomfort.

Skin: No significant irritation expected from a single short-term exposure.

Inhalation: No significant effects expected from a single short-term exposure.

Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: No known applicable information.

Inhalation: No known applicable information.



Page: 2 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

Oral: No known applicable information.

Other Health Effects

This product contains a chemical(s) that has the following effect(s): Reproductive Toxicity

See Section 11 for specific details.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS Number Wt % Component Name

57-11-4 1.0 - 5.0 Stearic acid

556-67-2 0.1 - 1.0 Octamethylcyclotetrasiloxane

The ingredients listed above are controlled products as defined in CPR, am. SOR/88-555.

4. FIRST AID MEASURES

Eye: If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. Obtain

medical attention.

Skin: No health effects expected. If irritation does occur flush with lukewarm, gently flowing water

for 5 minutes. If irritation persists, obtain medical advice.

Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air. If

irritation persists, obtain medical advice.

Oral: If irritation or discomfort occur, obtain medical advice.

Notes to Physician: Treat according to person's condition and specifics of exposure.

5. FIRE-FIGHTING MEASURES



Page: 3 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

Flash Point: $> 212 \,^{\circ}\text{F} / > 100 \,^{\circ}\text{C} \text{ (Closed Cup)}$

Autoignition Temperature: Not available.

Flammability Limits in Air: Not available.

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide

(CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large

fires involving chemicals. Determine the need to evacuate or isolate the area according to

your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire Hazards: None.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8.

Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, provincial, federal laws and regulations may apply to releases and disposal of this material, as well as those materials

and items employed in the cleanup of releases.

Note: See Section 8 for Personal Protective Equipment for Spills. Refer to Section 1 to obtain telephone numbers, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Avoid eye contact.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Consult local authorities for acceptable provincial values.

<u>CAS Number</u> <u>Component Name</u> <u>Exposure Limits</u>

57-11-4 Stearic acid None established.



Page: 4 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

LD50: > 5,000 mg/kg - Dermal Rabbit LD50: 23 mg/kg - Intravenous Mouse

556-67-2 Octamethylcyclotetrasiloxane Dow Corning guide: TWA 10 ppm.

LC50: 36 mg/l - Inhalation Rat; 4hr vapor

LD50: > 5,000 mg/kg - Oral Rat LD50: > 4,640 mg/kg - Dermal Rabbit

Engineering Controls

Local Ventilation: None should be needed.

General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Suitable Gloves: Handle in accordance with good industrial hygiene and safety practices.

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

Personal Protective Equipment for Spills

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable

Respirator:

No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Use reasonable care.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste

Color: White

Odor: Not available Odor Threshold: Not available.

Specific Gravity @ 25°C: 1.39

Viscosity: Not available.



Page: 5 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

Freezing/Melting Point: Not available.

Boiling Point: Not available.

Vapor Pressure @ 25°C: Not available.

Vapor Density: Not available. Evaporation Rate: Not available. Solubility in Water: Not available. Coefficient of Water/Oil Not available.

Distribution:

pH: Not available.

Volatile Content: Not available.

Flash Point: > 212 °F / > 100 °C (Closed Cup)

Autoignition Temperature: Not available. Flammability Limits in Air: Not available.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing

specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous polymerization will not occur.

Polymerization:

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde. Silicon dioxide.

11. TOXICOLOGICAL INFORMATION

Component Toxicology Information

Octamethylcyclotetrasiloxane administered to rats by inhalation at concentrations of 500 and 700 ppm resulted in statistically significant decreases in the number of pups born and the live litter size in both the first and second generations. Prolonged estrous cycles, and decreased mating and fertility indices were observed following 700 ppm exposure in the second generation only. There were also increases in the incidence of deliveries of offspring extending over an unusually long time period (dystocia).

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only.



Page: 6 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans.

Based on the available information on its potential to cause harm to human health, Health Canada, in a 2008 screening assessment, has concluded that octamethylcyclotetrasiloxane is not entering the environment in a quantity or concentration or under conditions that constitute or may constitute a danger in Canada to human life or health (http://www.ec.gc.ca/substances/ese/eng/challenge/batch2/batch2 556-67-2.cfm).

Repeated exposure in rats to D4 resulted in what appears to be protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Special Hazard Information on Components

Reproductive Toxicity

CAS Number Wt % Component Name

556-67-2 0.1 - 1.0 Octamethylcyclotetrasiloxane

Evidence of reproductive effects in

laboratory animals.

12. ECOLOGICAL INFORMATION

Environmental Fate and Distribution

Air: This product is a solid consisting of a high molecular weight silicone polymer and other solid

materials. Unless milled to produce a dust or particles, it is unlikely to give rise to atmospheric

contamination.

Water: This product is a solid which is completely insoluble in water. As the specific gravity is >1, it

will sink to the bottom of the water course.

Soil: This product will enter the terrestrial environment if, as a component of municipal or industrial

solid waste the product is landfilled. It is unlikely that further significant transformation of the

product will occur.

Degradation: High molecular weight polymer which is amenable to recycling. The product is not

biodegradable. The product is removed >80% during the sewage treatment process.

Environmental Effects

Toxicity to Water

Organisms:

This product has low water solubility and should not present a risk to aquatic organisms.

Toxicity to Soil Organisms: This product is a solid and does not contain significant concentrations of water soluble

constituents that may be leached from the product. It is therefore not likely to present a danger

to terrestrial organisms.



Page: 7 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

Bioaccumulation: This product is a solid which is not soluble in water and if ingested will not be absorbed.

Fate and Effects in Waste Water Treatment Plants

This product is a solid rubber type material which is unlikely to have any adverse effect on bacteria.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS

Can be incinerated in accordance with local regulations.

Call local hazardous waste disposal company or provincial waste authorities for more information. Refer to Section 1 to obtain telephone numbers, if additional information is required.

14. TRANSPORT INFORMATION

Canada Road (Based on IMDG Regulations)

Not subject to local road regulations.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Refer to Section 1 to obtain telephone numbers, if additional information is required.

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by the CPR.

WHMIS Class D, Division 2, Subdivision A.

CLASSIFICATION:

DSL Status: All chemical substances in this material are included on or exempted from the DSL.



Page: 8 of 8 Version: 2.6

Revision Date: 2011/01/04

DOW CORNING(R) 744 RTV SEALANT WHITE

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA

Inventory of Chemical Substances.

16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark