



Emergency Telephone  
(516) 249-9000

# SUBSTANCE DATA SHEET

*INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY*

NAME: SAR Insulation Adhesive  
TYPE: Modified Elastomer Soln.  
APPLICATION: Solvent Cement Heat Resistant Sprayable Insul. Adh. ISSUE DATE: 8-30-85

## PHYSICAL DATA

Viscosity, Brookfield	#4/20RPM/77F: 2000-3000CPS
Solids, CMPD Adhesives (Infra-Red)	32.0-34.0%
Weight Per Gallon	6.4-6.6 Lbs.
Flashpoint	< 20 F Setaflash
SIGNAL WORD Storage Life at 70 F	6 Months

DANGER!

## HAZARDOUS INGREDIENTS

### HEXANE

ACGIH Exposure Limit: 50 PPM, 8-HR TWA  
OSHA 29CFR1910 Exposure Limit: 500 PPM, 8-HR TWA  
NIOSH Document Number: 77-151

## STATEMENT OF HAZARDS

May cause irritation of skin, eyes, nose, and throat. Prolonged or repeated exposure to Hexane has been reported to cause severe nerve disorders.

## HANDLING PRECAUTIONS

Avoid prolonged or repeated breathing of vapor. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

## PERSONAL PROTECTION

"Rubber" gloves and respiratory protection.



- FIRST AID**      **Eyes and Skin:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. Flush skin with water. Wash clothing before re-use.  
**Internal:** If swallowed, do not induce vomiting. Call a physician.  
**Inhalation:** Remove to fresh air.
- FIRE HAZARD**      **Extremely flammable.** Keep away from heat, sparks, and flame. In case of fire, use water spray, foam, dry chemical, or CO2.

#### STORAGE PRECAUTIONS

Keep container closed. Store in a cool, dry place.  
Limited storage life—refer to product specifications.

#### SPILL INFORMATION

Eliminate all ignition sources. Prevent entry into natural bodies of water.

#### WASTE DISPOSAL

Recover free liquid. Absorb residue and discard according to Federal, State, and Local regulations. Empty container: May contain explosive vapors. Do not cut, puncture, or weld on or nearby.

#### DISCLAIMER

The information and recommendations contained herein are offered as a service to our customers, but are not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of these materials. The information and recommendations provided herein were believed by Duro Dyne to be accurate at the time of preparation or obtained from sources believed to be generally reliable. However, Duro Dyne makes no warranty concerning their accuracy and Duro Dyne will not be liable for claims relating to any party's use of or reliance on information or recommendations contained herein, regardless of whether it is claimed that the information or recommendations are inaccurate, incomplete or otherwise misleading.