

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

Trade Name: OATEY PIPE SEAL
Product No.: 30614
Product Use: Caulking lead substitute for cast iron soil pipe joints
Formula: See Section 2
Synonyms: Soil pipe seal
Firm Name & Mailing Address: OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland, Ohio 44135, U.S.A. <http://www.oatey.com>
Oatey Phone Number: (216) 267-7100 or (800) 321-9532
Emergency Phone Numbers: For Emergency First Aid call 1-303-623-5716 COLLECT. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1-703-527-3887.
Prepared By: Corporate Director - Safety and Environmental Compliance
Preparation Date: March 12, 2011

SECTION 2

COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENTS:</u>	<u>%wt/wt:</u>	<u>CAS NUMBER:</u>	<u>ACGIH TLV TWA:</u>	<u>OSHA PEL TWA:</u>	<u>OTHER:</u>
Kaolin Clay	40 - 70%	1332-58-7	2 mg/m3	15 mg/m3 (total dust)	None
Methyl Ethyl Ketone	15 - 40%	78-93-3	200 ppm 300 ppm STEL	200 ppm	None
Vinyl Chloride	7 - 13%	25085-82-9	None	None	None
Acetate Resin			Established	Established	
Amorphous Silica (Non-hazardous)	1 - 5%	112945-52-5	10 mg/m3	20 mppcf	None
Gray Pigment (Non-hazardous)	0.1 - 1%	Not Available	None	None	None

OSHA Hazard Classification: Flammable, irritant, organ effects

SECTION 3

HAZARDS IDENTIFICATION

Emergency Overview:
Heavy gray paste with a ketone odor. Extremely flammable liquid and vapor. Vapors may cause flash fire. May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects. Swallowing may cause irritation, nausea, vomiting, diarrhea and kidney or liver disorders. Aspiration hazard. May be fatal if swallowed. Symptoms may be delayed.

SECTION 4

FIRST AID MEASURES

CALL 1-303-623-5716 COLLECT

Skin: Remove contaminated clothing immediately. Wash all exposed areas with soap and water. Get medical attention if irritation develops. Remove dried cement with Oatey Plumber's Hand Cleaner or baby oil.

Eyes: If material gets into eyes or if fumes cause irritation, immediately flush eyes with plenty of water until chemical is removed. If irritation persists, get medical attention immediately.

Inhalation: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.

Ingestion: **DO NOT INDUCE VOMITING.** Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

SECTION 5 FIRE FIGHTING MEASURES

Flashpoint / Method: 52 Degrees F. (11 Degrees C) / PMCC
Flammability: LEL = 2.0 % Volume, UEL = 12.0 % Volume
Extinguishing: Use dry chemical, CO2, or foam to extinguish fire. Cool fire
Media: exposed container with water. Water may be ineffective as an
extinguishing agent.
Special Fire: Firefighters should wear positive pressure self-contained
Fighting: breathing apparatus and full protective clothing for fires in
Procedure: areas where chemicals are used or stored
Unusual Fire and: Extremely flammable liquid. Keep away from heat and all
Explosion: sources of ignition including sparks, flames, lighted
Hazards: cigarettes and pilot lights. Containers may rupture or
explode in the heat of a fire. Vapors are heavier than air
and may travel to a remote ignition source and flash back.
Hazardous: Combustion will produce toxic and irritating vapors including
Decomposition: carbon monoxide and carbon dioxide.
Products:

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill or: Remove all sources of ignition and ventilate area. Stop leak if it
Leak: can be done without risk. Personnel cleaning up the spill should
Procedures: wear appropriate personal protective equipment, including respirators
if vapor concentrations are high. Soak up spill with an inert
absorbent such as sand, earth or other non-combusting material. Put
absorbent material in covered, labeled metal containers. Prevent
liquid from entering watercourses, sewers and natural waterways.
Report releases to authorities as required. See Section 13 for
disposal information.

SECTION 7 HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors
or mists. Use with adequate ventilation (equivalent to outdoors).
Wash thoroughly after handling. Do not eat, drink or smoke in the
work area. Keep product away from heat, sparks, flames and all other
sources of ignition. No smoking in storage or use areas. Keep
containers closed when not in use.
Storage: Store in a cool, dry, well-ventilated area away from incompatible
materials. Keep containers closed when not in use.
Other: "Empty" containers retain product residue and can be hazardous.
Follow all MSDS precautions in handling empty containers. Do not cut
or weld on or near empty or full containers.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Open doors & windows. Provide ventilation capable of maintaining
emissions at the point of use below recommended exposure limits. If
used in enclosed area, use exhaust fans. Exhaust fans should be
explosion-proof or set up in a way that flammable concentrations of
solvent vapors are not exposed to electrical fixtures or hot
surfaces.
Respiratory: For operations where the exposure limit may be exceeded, a NIOSH
Protection: approved organic vapor respirator or supplied air respirator is
recommended. Equipment selection depends on contaminant type and
concentration, select in accordance with 29 CFR 1910.134 and good
industrial hygiene practice. For firefighting, use self-contained
breathing apparatus.
Skin: Rubber gloves are suitable for normal use of the product. For long
Protection: exposures chemical resistant gloves may be required such as
4H(tm) or Silver Shield(tm) to avoid prolonged skin contact.
Eye: Safety glasses with side shields or safety goggles.
Protection:

SECTION 8 (Continued)

Other: Eye wash and safety shower should be available.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 178 Degrees F / 81 Degrees C
Melting Point: Not applicable
Vapor Pressure: Not determined
Vapor Density: (Air = 1) 2.5
Volatile Components: 23-27%
Solubility In Water: Negligible
pH: Not applicable
Specific Gravity: 0.87 +/- 0.02 @ 20 Degrees C
Evaporation Rate: Not determined
Appearance: Heavy Gray Paste
Odor: Sharp-penetrating odor
Will Dissolve In: Acetone or Methyl Ethyl Ketone
Material Is: Paste

SECTION 10 STABILITY AND REACTIVITY

Stability: Stable.
Conditions To Avoid: Avoid heat, sparks, flames and other sources of ignition.
Hazardous: Combustion will produce toxic and irritating vapors
Decomposition: including carbon monoxide and carbon dioxide.
Products:
Incompatibility/ Oxidizing agents, alkalis, amines, ammonia, acids, chlorine
Materials To Avoid: compounds, chlorinated inorganics (potassium, calcium and
sodium hypochlorite) and hydrogen peroxides. May attack
plastic, resins and rubber.
Hazardous: Will not occur.
Polymerization:

SECTION 11 TOXICOLOGICAL INFORMATION

Inhalation: Vapors or mists may cause mucous membrane and respiratory irritation, coughing, headache, dizziness, dullness, nausea, shortness of breath and vomiting. High concentrations may cause central nervous system depression, narcosis and unconsciousness. May cause kidney, liver and lung damage.
Skin: May cause irritation with redness, itching and pain. Methyl ethyl ketone may be absorbed through the skin causing effects similar to those listed under inhalation.
Eye: Vapors may cause irritation. Direct contact may cause irritation with redness, stinging and tearing of the eyes. May cause eye damage.
Ingestion: Swallowing may cause abdominal pain, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting can cause chemical pneumonia and lung damage. May cause kidney and liver damage.
Chronic: Prolonged or repeated overexposure cause dermatitis and damage
Toxicity: to the kidney, liver, lungs and central nervous system.
Toxicity Data: Methyl Ethyl Ketone: Oral rat LD50: 2,737 mg/kg
Inhalation rat LC50: 23,500 mg/m3/8 hours
Skin rabbit LD50: 6,480 mg/kg
Sensitization: None of the components are known to cause sensitization.

SECTION 11 (Continued)

Carcinogenicity: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.
Mutagenicity: Methyl ethyl ketone is generally thought not to be mutagenic.
Reproductive Toxicity: Methyl ethyl ketone has been shown to cause embryofetal toxicity and birth defects in laboratory animals.
Medical Conditions: Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to this product.
Aggravated By Exposure:

SECTION 12 ECOLOGICAL INFORMATION

This product is not expected to be toxic to aquatic organisms.
Methyl Ethyl Ketone: 96 hour LC50 for fish is greater than 100 mg/L.
VOC Information: This product emits VOC's (volatile organic compounds) in its use. Make sure that use of this product complies with local VOC emission regulations, where they exist.
VOC Level: Not determined.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with current local, state and federal regulations.
RCRA Hazardous Waste Number: U159
EPA Hazardous Waste ID Number: D001, D035, F005
EPA Hazard Waste Class: Ignitable Waste. Toxic Waste (Methyl Ethyl Ketone content)

SECTION 14 TRANSPORT INFORMATION

DOT	<u>Less than 1 Liter (0.3 gal)</u>	<u>Greater than 1 Liter (0.3 gal)</u>
Proper Shipping Name:	Consumer Commodity	Adhesives
Hazard Class/Packing Group:	ORM-D	3, PGIII
UN/NA Number:	None	UN1133
Hazard Labels:	None	Flammable Liquid
IMDG		
Proper Shipping Name:	Adhesives	Adhesives
Hazard Class/Packing Group:	3, III	3, III
UN Number:	UN1133	UN1133
Label:	None (Limited Quantities are excepted from labeling)	Class 3 (Flammable Liquid)

2004 North American Emergency Response Guidebook Number: 127 or 128

SECTION 15 REGULATORY INFORMATION

Hazard Category for Section 311/312: Acute Health, Chronic Health, Flammable
Section 302 Extremely Hazardous Substances (TPQ): This product does not contain chemicals regulated under SARA Section 302.
Section 313 Toxic Chemicals: This product does not contain chemicals subject to SARA Title III Section 313 Reporting Requirements.
CERCLA 103 Reportable Quantity: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Methyl Ethyl Ketone (32% maximum) of 5,000 lbs, is 15,625 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.
California Proposition 65: This product does not contain any chemicals subject to the California Proposition 65 regulation.
TSCA Inventory: All of the components of this product are listed on the TSCA inventory.
Canadian WHIMS Classification: Class B, Division 2; Class D, Division 2, Subdivision A; Class D, Division 2, Subdivision B. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

SECTION 16 OTHER INFORMATION

NFPA and HMIS:
NFPA Hazard Signal: Health: 1 Flammability: 3 Reactivity: 0 Special: None
HMIS Hazard Signal: Health: 2* Flammability: 3 Reactivity: 0 PPE: G

DISCLAIMER

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, Oatey cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.