

MSDS Material Safety Data Sheet

UNITEX

PRO-POLY

Page 1 of 5

MSDS Number: 1037

Revision Date: 11/21/2005

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

UNITEX
3101 Gardner Ave.

Kansas City, MO 64120

Contact: Technical Services

Telephone Number: 800-821-5846

FAX Number: 816-483-3149

E-Mail: mail@unitex-chemicals.com

Web www.unitex-chemicals.com

Supplier Emergency contacts & Phone

Contact #1 800-555-4545

Contact #2

EMERGENCY CONTACT: CHEMTREC 24 hrs. Phone No.:1-800-424-9300

HAZARD RATINGS: HEALTH (2) FIRE (3) REACTIVITY (0) EQUIPMENT (B)

2

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perc.

Part A		
Trade Secret	Modified Acrylic Polymer	70-90%
14808-60-7	Silica	10-30%
Part B		
14808-60-7	Silica	50-70%
Trade Secret	Modified Amine	30-50%

None of the remaining components are not considered a hazard.

MSDS Material Safety Data Sheet

UNITEX

PRO-POLY

Page 2 of 5

MSDS Number: 1037

Revision Date: 11/21/2005

3 HAZARDS IDENTIFICATION

Route of Entry: Eyes, Skin, Ingestion, Inhalation
Target Organs: None known
Inhalation: May cause irritation to nose and throat.
Skin Contact: May cause irritation and dermatitis.
Eye Contact: May cause irritation, sensitization and may lead to eye damage.
Ingestion: May cause irritation of the mouth, stomach and sensitization.

OSHA Regulation 29 CFR 1910.1000 Requires the following permissible exposure limits:

Modified Acrylic Polymer CAS No.: Trade Secret	OSHA/ACGIH (TWA/STEL) Not established
Silica CAS No.: 14808-60-7	OSHA/ACGIH (TWA/STEL) 10 mg/m3 - 0.05 mg/m3
Modified Amine CAS No.: Trade Secret	OSHA/ACGIH (TWA/STEL) Not established

4 FIRST AID MEASURES

Inhalation: If overexposure occurs, remove victim to fresh air. If breathing stops, administer artificial respiration. Seek immediate medical attention. Symptoms may include difficulty breathing, coughing, excessive sneezing, soreness of the throat, tightness in chest and respiratory failure.

Skin Contact: Remove contaminated clothing as soon as possible. Wash exposed skin thoroughly with soap and water. If irritation persists, consult a physician. Launder contaminated clothing before reuse. Extremely contaminated clothing should be discarded. Symptoms may include redness, dermatitis, blistering and severe irritation.

Eye Contact: Flush eyes with plenty of water for at least 15 minutes. If necessary, gently hold open eyelids during the flush. Immediately seek medical attention.

Ingestion: If large amounts of material is swallowed, do not induce vomiting. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into the lungs. Immediately consult a physician. Do not attempt to give liquid to an unconscious person.

5 FIRE FIGHTING MEASURES

Flash Point:	A: 250 deg. F.	B: 176 deg. F.
Flash Point Method:	Pensky Martins Closed Cup Method	
Burning Rate:	No data available	
Autoignition Temperature:	No data available	
LEL:	No data available	
UEL:	No data available	
Flammability Classificati	A: Combustible Liquid	

Other:

Special Fire Fighting Procedures: None. Avoid breathing smoke. NFPA Class B - extinguisher (dry chemical or foam) for class 1C fires. Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers. Use fog nozzles if water is used. Use supplied breathing masks. At higher temperature, pressure builds up in sealed containers. NOTE: Flammable/Combustible liquid can release vapors that form flammable/combustible mixtures at temperatures at or above the flashpoint. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

MSDS Material Safety Data Sheet

UNITEX

PRO-POLY

Page 3 of 5

MSDS Number: 1037

Revision Date: 11/21/2005

6 ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Contain spill with inert materials (sand, vermiculite, etc.). Sweep or scoop up and put into containers. Keep containers closed with material covered with a water blanket.

7 HANDLING AND STORAGE

Handling Precautions: For professional use only. Use as directed. Avoid eye/skin contact. Wash after using and before eating or smoking. Avoid breathing vapors. Avoid uncontrolled mixing. Respiratory protection is required when ventilation is inadequate. NIOSH/OSHA approved organic vapor respirators should be provided and worn.

Storage Requirements: Store in a cool/dry location. Store away from sparks and open flames.

Containers of this material may be hazardous when emptied. Since containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a lab hood. Provide mechanical ventilation of confined spaces.

Protective Equipment: RESPIRATORY PROTECTION: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear OSHA/NIOSH approved organic vapor respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen.

PROTECTIVE CLOTHING/EQUIPMENT: Wear chemically protective gloves, boots, aprons to prevent prolonged or repeated skin contact. Wear protective goggles and face shield, per OSHA eye and face protection regulations (29 CFR 1910.133). Wear butyl rubber, nitrile rubber or polyethylene gloves.

CONTAMINATED EQUIPMENT: Remove contaminated clothes immediately. Launder before reuse.

OTHER PRECAUTIONS: Never eat, drink or smoke in work areas.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: A: White B: Clear

Physical State: Paste/Gel

Odor: A: Mild B: Acrylic

pH: Not applicable

Vapor Pressure: Not determined

Vapor Density: Not determined

Boiling Point: No data available

Freezing/Melting Pt.: Not applicable

Solubility: Slight

Spec Grav./Density: A: 1.063 g/cc B: 0.984 g/cc

Viscosity: A: 49000 cps B: 25000 cps
Percent Volatile: A: 6.15% B: 39.86% ASTM D2369@110 C

MSDS Material Safety Data Sheet

UNITEX

PRO-POLY

Page 4 of 5

MSDS Number: 1037

Revision Date: 11/21/2005

10 STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	Heat and Flames.
Materials to avoid (incompatibility):	Strong acids
Hazardous Decomposition products:	Carbon Monoxide, Carbon Dioxide and oxides of Nitrogen. Gases may contain toxic vapors and gases particles.
Hazardous Polymerization:	Will not occur with normal handling.

11 TOXICOLOGICAL INFORMATION

No data available

12 ECOLOGICAL INFORMATION

No data available

13 DISPOSAL CONSIDERATIONS

Consult municipal authorities, landfill personnel, disposal companies prior to any disposal activity. Always follow local, state and federal regulations. Waste must be incinerated.

14 TRANSPORT INFORMATION

Consult DOT 49 CFR 172.101 for transportation information.

MSDS Material Safety Data Sheet

UNITEX

PRO-POLY

Page 5 of 5

MSDS Number: 1037

Revision Date: 11/21/2005

15

REGULATORY INFORMATION

This MSDS has been prepared in accordance with federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

HMIS Codes: Health (2) Flammability (3) Reactivity (0) PPE (C)

Fire Hazard: Yes
Pressure: No
Reactivity: No
Acute: Yes
Chronic: No

This product contains the following components listed as Extremely Hazardous Air Pollutants:
NONE

SARA Section 302:

This product contains the following components listed as Extremely Hazardous Substances:
None

SARA Section 311/312:

Hazard Classification: Fire

SARA Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: NONE

TSCA:

This product or its components are listed in or exempt from the TSCA inventory requirements.

New Jersey:

This product contains the following non-hazardous components subject to disclosure under New Jersey Right-To-Know legislation:
None

Pennsylvania:

This product contains the following non-hazardous components subject to disclosure under Pennsylvania Right-To-Know legislation: None

California (Proposition 65):

This product contains the following substances known to the State of California to cause cancer: None

16

OTHER INFORMATION

The information and recommendations in this document are based in the best available to us at the time of preparation. We make no other warranty, expressed or implied, as to the correctness or completeness, or as the results or reliance of this product.

END OF MSDS DOCUMENT