## **Material Safety Data Sheet**

MSDS ID: 41744

Product Name: VINYL MASTIC WEATHER BARRIER - WC-5, COLORS

Section 1 - Product and Company Identification					
Sec. 01 Product Name :	VINYL MASTIC WEATHER BARRIER - WC-5, COLORS				
Sunanuma					
Synonyms :					
Chemical Name :	NO DATA SUPPLIED				
Chaminal Familia					
Chemical Family :					
	ç <u></u>				
Sec. 01 Name :	VIMASCO CORPORATION				
Division :					
Address Line 1 :	P.O. BOX 516				
Address Line 2 :	:				
City:	NITRO				
State / Province :					
	· · · · · · · · · · · · · · · · · · ·				
ZIP code :	25143 Country :				
Emergency and					
Other Phone :	304-755-3328 (EMERGENCY) 304-755-3328 (NIGHT EMERGENCY)				
Telex :	Fax:				
Telex .	Fax .				
Sec. 01 Product Use :					
Sec. 01 Product Use :	·				
	<u> </u>				
Chemtrec Number :	! :				
MSDS Prepared by:					
Effective Date :	8/29/90				
Additional Information :	12 MAR 1998				
	PRODUCT CLASS: LATEX-BASED COATING (MIXTURE)				
	FORMULA/CAS: NO DATA SUPPLIED				
DATE ISSUED: 08-29-90					
	DATE ISSUED: 00-29-90 DATE ENTERED: 11-15-96				
	MATERIAL SAFETY DATA SHEET FOR COATINGS, RESINS, AND RELATED				
	MATERIALS				

Product Name: VINYL MASTIC WEATHER BARRIER - WC-5, COLORS

Sec. 01

Manufacturer Product Product Code

Numbers :

Description

s: WC-5, COLORS

2336

SUPPLIER PART

NO DATA SUPPLIED

Section 2 - Composition Information

Additional Information: INGREDIENT INFORMATION

CHLORINATED PARAFFIN

%: 5

VINYL ACETATE %: 0.02 ACRYLATE %: ND

TRI(B-CHLOROETHYL)PHOSPHATE

%: 5

INGREDIENT HAZARD STATEMENT

ND = NO DATA

NOT EST. = NOT ESTABLISHED

\* (TWA=ACGIH)

HAZARDOUS INGREDIENTS:

INGREDIENT VAPOR PRESSURE CHLORINATED PARAFFIN NOT AVAILABLE VINYL ACETATE (RESIDUAL NOT AVAILABLE

MONOMER)

ACRYLATE (RESIDUAL MONOMER)

[CAS NO. 9003-1-4] (SIC)

TRI)B-CHLOROETHYL)PHOSPHATE 17.5MMHG @ 70 DEG. F

Section 3 - Hazards Identification Sec. 03 **Emergency** Overview: Relevant Routes ROUTES OF ENTRY of Exposure: INHALATION? YES SKIN? YEŞ INGESTION? NO DATA SUPPLIED NO DATA SUPPLIED EYES? ADDITIONAL INFORMATION PRIMARY ROUTES OF ENTRY: DERMAL, INHALATION PLEASE REFER TO ACUTE AND CHRONIC HEALTH HAZARDS. Symptoms of Acute Overexposure: Signs and Symptoms of Chronic Overexposure: Medical Conditions MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: NONE Aggravated: KNOWN.

MSDS ID: 41744 Product Name: VINYL MASTIC WEATHER BARRIER - WC-5, COLORS Sec. 03 Eyes: Skin: Ingestion: Inhalation: Sec. 03 NTP: N IARC: N OSHA: N ACGIH: Other: Additional CARCINGGENICITY Information: NO DATA SUPPLIED ACUTE AND CHRONIC HEALTH HAZARDS EFFECTS OF OVEREXPOSURE: A TLV FOR THIS MIXTURE HAS NOT BEEN ESTABLISHED. THEREFORE, THE FOLLOWING EFFECTS ARE THOSE OF THE INDIVIDUAL COMPONENTS OF SECTION 2. CHLORINATED PARAFFIN: UNDER NORMAL USE, CONSIDERED NONTOXIC BY ANY ROUTE OF EXPOSURE. CHRONIC EXPOSURE WOULD SUGGEST A SLIGHT HAZARD WITH THE LIVER BEING THE PROBABLE TARGET ORGAN. VINYL ACETATE & ACRYLATE (RESIDUAL MONOMER): SLIGHT RESIDUAL MONOMER CAN CAUSE EYE AND RESPIRATORY IRRITATION AT HIGH AIR CONCENTRATIONS. TRI(B-CHLOROETHYL)PHOSPHATE: MILDLY IRRITATING TO SKIN (LD50 RABBITS <2150 MG/KG). INGESTION: LD50 RATS 500 MG/KG. TREMORS, MUSCULAR SPASMS, LABORED BREATHING, LACRIMATION, SALIVATION, AND EXCESS URINATION. Section 4 - First Aid Measures Sec. 04 Eyes: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

Sec. 04

Eyes: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

Skin: WASH WITH SOAP AND WATER.

Ingestion: GIVE TWO GLASSES OF WATER, INDUCE VOMITING, CONSULT PHYSICIAN OR POISON CONTROL CENTER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Inhalation: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

MSDS ID: 41744 Product Name: VINYL MASTIC WEATHER BARRIER - WC-5, COLORS Sec. 04 Antidotes: Notes to Physician and/or Protection for First Aiders: Additional Information Section 5 - Fire Fighting Procedures Flammable Limits in LEL: NOT AVAILABLE UEL: NO DATA SUPPLIED Sec. 05 Air (Percent by volume): Flammability OSHA - IIIB DOT - NOT REGULATED Classification: Autoignition NO DATA SUPPLIED Sec. 05 Temperature: Flash Point: NO FLASH TO BOILING, 212 DEGREES F Flash Point Method: (TCC) Sec. 05 Extinguishing FOAM ALCOHOL FOAM CO2 DRY CHEMICAL WATER FOG Media: Fire Fighting PRODUCT WILL NOT BURN UNTIL WATER HAS BOILED OR EVAPORATED. FOR Instructions: DRIED FILM RESIDUAL SOLIDS, FULL PROTECTIVE EQUIPMENT IS RECOMMENDED, INCLUDING SELF-CONTAINED BREATHING APPARATUS. Unusual Fire and NONE KNOWN Explosion Hazards: Combustion By-Products:

Product Name: VINYL MAS	STIC WEATHER BARRIER - WC-5, COLORS
Sec. 05 Burning Rate	;
Combusting Properties	;
Addtional Information	NFPA HAZARD CLASSIFICATION : FLAMMABLE: NO HEALTH: NO REACTIVITY: NO SPECIAL: NO
	Section 6 - Accidental Release Measures
Sec. 06 Accidental Release	: STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
	MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL. MINOR SPILLS MAY BE FLUSHED TO SEWER IF REGULATIONS PERMIT. BEFORE DRYING, PRODUCT MAY BE WASHED AWAY WITH WATER; AFTER DRYING, REMOVE WITH A PAINT SCRAPER OR STRONG SOLVENT.
Large Spill	•
24.30 04	
Carall Caill	
Small Spill	
B	,
Persona Precautions	
riecadions	• :
Environmenta	
Precautions	<b>:</b> -
Prohibited Products	
Clean-up Methods	
Additional Information	
Additional Information	:
	Section 7 - Handling and Storage
Sec. 07 Handling Precautions	PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING VAPORS AND APPLICATION TO HOT SURFACES, AS VAPORS MAY BE IRRITATING. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. STORE INDOORS AT TEMPERATURES OF 45 DEGREES - 90 DEGREES F.
Storage Precautions	SEE "HANDLING PRECAUTIONS" HEREIN.
Other Precautions	NO DATA SUPPLIED
Additional Information	

Product Name: VINYL MASTIC WEATHER BARRIER - WC-5, COLORS

tion8 - Exposure Control / Personal Protection	
;	
SPECIAL EXHAUST: NO DATA SUPPLIED	
MECHANICAL EXHAUST: GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE SATISFACTORY.  GOGGLES, FACESHIELD, OR OTHER EYEWEAR TO PROTECT FROM SPLASH.	
GLOVES: PROTECTIVE GLOVES: IMPERVIOUS GLOVES	
IN RESTRICTED VENTILATION AREAS, USE APPROVED CHEMICAL VAPOR RESPIRATOR. IN APPLICATIONS WHERE MISTS OR SPRAY MAY BE GENERATED, AVOID INHALATION OF AIRBORNE PARTICULATES BY USING AN APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE WITH PREFILTER FOR MIST OR DUST.	
OTHER PROTECTION NO DATA SUPPLIED	
CLOTHING OTHER PROTECTIVE EQUIPMENT: NONE HYGIENIC PRACTICES: THOROUGHLY CLEANSE HANDS AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.	
<u> </u>	
ection 9 - Physical and Chemical Properties	
DATA SUPPLIED	
DATA SUPPLIED	
DATA SUPPLIED	
J	

Product Name: VINYL MA	ASTIC WEATHER BARRIER - WC-5, COLORS
Sec. 09 Boiling Point :	212 DEGREES F (RANGE)
Melting Point :	NO DATA SUPPLIED
Softening Point :	
Freezing Point :	25 DEGREES F (-4 DEGREES C)
VOC Content :	
Percent Volatile :	.50% (VOLUME)
pH Value :	18.0-9.0
Sec. 09 Specific Gravity :	1.23
Vapor Pressure :	PLEASE REFER TO SECTION 2 (MM HG)
Vapor Density :	LIGHTER THAN AIR (AIR=1)
Saturated Vapor Concentration :	
Evaporation Rate :	
Evaporation Basis :	BUTYL ACETATE
Water Solubility :	APPRECIABLE
Water Reactivity :	
Oil Coeff :	
Octanol/Water Coeff:	
	APPROX. 80,000 CENTIPOISE SPRAY GRADE; APPROX. 175,000 CENTIPOISE
Decomposition Temp :	TROWEL GRADE
Heat Value :	
Bulk Density :	
Weight per Gallon :	10.2 LBS.
Additional Information	EVAPORATION RATE: SLOWER THAN ETHER
•	DECOMPOSITION TEMPERATURE: APPROX. 240 DEGREES F. (115 DEGREES C.)
	CHEMICAL DESCRIPTOR: MIXTURE LIQUID  Section 10 - Stability and Reactivity
Soc 10	
Sec. 10 Stabil	ity: PRODUCT IS STABLE.

MISUS (U: 41/44	
Product Name: VINYL MAST	FIC WEATHER BARRIER - WC-5, COLORS
Stability Condition to Avoid	S NONE KNOWN.
Polymerization	1: HAZARDOUS POLYMERIZATION WILL NOT OCCUR
Polymerizatio Conditions to Avoid	n NONE KNOWN.
Incompatibility wit other materials	h MATERIALS INCOMPATIBLE WITH WATER.
Decomposition	S OR BY-PRODUCTS: THERMAL DECOMPOSITION WILL YIELD CO, CO2, HCL, HPOX, ANTIMONY- COXYCHLORIDE, AND FRAGMENTED, SHORT-CHAIN HYDROCARBONS.
Additional Informatio	
	Section 11 - Toxicological Information
Sec. 11 Toxicologica Information	al
Additional Information	n:
OTHER Animal LC50 LD50	Value Units Routes Components
	Section 12 - Ecological Information
Sec. 12 Ecologica Information	
Additional Information	1

Product Name: VINYL MASTIC WEATHER BARRIER - WC-5, COLORS

Sec. 13	Disposal Considerations :	IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. REVIEW HAZARD SECTION OF THIS SHEET BEFORE ATTEMPTING CLEAN-UP. EMPTY CONTAINERS ARE NON HAZARDOUS UNDER RCRA AS INDUSTRIAL WASTE.			
1	Additional Information :				
:					
		Section 14 - Transportation Information			
Sec. 14	Basic Shipping Description :				
	Proper Shipping Name	<u></u>			
•					
	Hazard Class :				
:	DOT ID :	Packing Group :			
:	Label (s) :				
	Special Provisions :				
Sec. 14		Packaging and Stowage			
GCU. 14	DOT Exceptions :				
	Non-Bulk Packaging :				
	Bulk Packaging :				
	Air/Rail Limit :				
:	Cargo Air Limit :				
	Vessel Stowage :				
	Other Stowage :				
	Reportable Quantity :				
		! :			

MSDS ID: 41744	
Product Name: VINYL MASTIC	C WEATHER BARRIER - WC-5, COLORS
Sec. 14 JATA Name	
IATA Class :	IATA ID: IATA RISK:
IATA Packing Group :	
IATA Hazard Labels :	
IATA Special Provisions :	
Instructions :	Passenger or Cargo Aircraft  Max. Net Quantity:
Instructions :	Cargo Aircraft Only  Max. Net Quantity:
Sec. 14 IMO Name :	
IMO Class :	
IMO ID :	IMO Packing Group :
IMO Risk :	
IMO First Aid Guide :	
Additional Information :	DOT CLASSIFICATION: NOT REGULATED TRANSPORTATION INFORMATION:
1. 1. 2.11	SHIPPING CLASS 55, PAINT (NO SPECIAL LABELS REQUIRED)
	Section 15 - Regulatory Information  SARA STATUS: THIS MIXTURE CONTAINS THE FOLLOWING MATERIALS REGULATED UNDER SECTION 313: NONE
State :	
International :	
Immediate (Acute) Health :	
Delayed (Chronic) Health :	·····
Fire:	
Sudden Release of Presure :	
Reactive :	

MSDS ID : 41744	O MEATILED BARRIES	- Wo F 001 000	
Product Name: VINYL MASTIC			
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	Section 16	6 - Other	
Sec. 16 Health :			
	!		;
Flammability :	·		
Reactivity :	<u> </u>	<u> </u>	<u>ا</u> ٦٠٠٠
,,	ļ . ;		l
Special: 0			
——————————————————————————————————————			
	i		!
•			
Sec. 16 Health:		Reactivity :	
Flammability :		Protection :	
·			
Product Label			
Information :			. 1
Other Information :	HAZARD RATINGS -		
	H - HEALTH	· 1	:
	R - REACTIVITY	. 1	
Additional Information	PERSONAL PROTECT	HUN B	
<b>-</b>	:		