

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION
Trade Name: OATEY PLUMBER'S PUTTY
Product No.: 31166, 31170, 31174
Product Use: Stainless fixture setting compound.
Formula: See SECTION 2
Synonyms: Putty.
Firm Name & Mailing Address: OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland, Ohio 44135, U.S.A. <http://www.oatey.com>
Oatey Phone Number: (216) 267-7100 or (800) 321-9532
Emergency Phone Numbers: For Emergency First Aid call 1-303-623-5716 COLLECT. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the US: 1-703-527-3887.
Prepared By: Corporate Director - Safety and Environmental Compliance
Preparation Date: April 15, 2008

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENTS:</u>	<u>%wt/wt:</u>	<u>CAS NUMBER:</u>	<u>ACGIH TLV TWA:</u>	<u>OSHA PEL TWA:</u>	<u>OTHER:</u>
Limestone	60 - 90%	1317-65-3	10 mg/M3	15 mg/M3 (Total dust)	None
Hydrocarbon oil	10 - 30%	64742-52-5	5 mg/M3	5 mg/M3	None
Talc	1 - 5%	14807-96-6	2 mg/M3	2 mg/M3	None
Clay	1 - 5%	68953-58-2	10 mg/M3	10 mg/M3	None

OSHA Hazard Classification: Not hazardous

SECTION 3 HAZARDS IDENTIFICATION
Emergency Overview:
White putty with a mild petroleum odor. May cause mechanical irritation of the eyes.

SECTION 4 FIRST AID MEASURES
CALL 1-303-623-5716 COLLECT
Skin: Wash all exposed areas with soap and water.
Eyes: If material gets into eyes or if fumes cause irritation, immediately flush eyes with plenty of water until chemical is removed. If irritation persists, get medical attention immediately.
Inhalation: Not a likely route of entry.
Ingestion: **DO NOT INDUCE VOMITING.** Rinse mouth with water. Call a physician.

SECTION 5 FIRE FIGHTING MEASURES
Flashpoint / Method: Not applicable
Flammability: LEL = ND, UEL = ND
Extinguishing Media: Use dry chemical, CO2, or foam to extinguish fire. Cool fire exposed container with water. Water may be ineffective as an extinguishing agent.
Special Fire Fighting Procedure: As appropriate for surrounding fire.
Unusual Fire and Explosion Hazards: None
Hazardous Decomposition Products: Combustion will produce toxic and irritating vapors including carbon monoxide and carbon dioxide.

SECTION 11 TOXICOLOGICAL INFORMATION

Inhalation: Not a likely route of entry.
Skin: May cause mild irritation. Prolonged and repeated contact may cause dermatitis.
Eye: Contact may cause irritation.
Ingestion: Swallowing may cause a laxative effect including cramps and diarrhea.
Chronic Toxicity: Prolonged or repeated overexposure cause dermatitis.
Toxicity Data: Not available
Sensitization: None of the components are known to cause sensitization.
Carcinogenicity: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.
Mutagenicity: None of the components are known to be mutagenic.
Reproductive Toxicity: None of the components are known to be toxic to reproduction.
Medical Conditions Aggravated By Exposure: None known.

SECTION 12 ECOLOGICAL INFORMATION

No ecotoxicological information known.
VOC Information: This product has very low VOC level.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with current local, state and federal regulations.
RCRA Hazardous Waste Number: Not a hazardous waste.
EPA Hazardous Waste ID Number: Not a hazardous waste.
EPA Hazard Waste Class: Not a hazardous waste.

SECTION 14 TRANSPORT INFORMATION

DOT	<u>Less than 1 Liter (0.3 gal)</u>	<u>Greater than 1 Liter (0.3 gal)</u>
Proper Shipping Name:	Not regulated.	Not regulated.
Hazard Class/Packing Group:	None	None
UN/NA Number:	None	None
Hazard Labels:	None	None

IMDG

Proper Shipping Name:	Not regulated
Hazard Class/Packing Group:	None
UN Number:	None
Label:	None

2004 North American Emergency Response Guidebook Number: None

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION
Trade Name: OATEY No. 95 TINNING FLUX - LEAD FREE
Product No.: 30372, 30373, 30374, 30375, 53201
Product Use: Flux for pre-tinning copper pipe.
Formula: See Section 2
Synonyms: Flux for Soldering Copper Pipe
Firm Name & Mailing Address: OATEY CO. 4700 West 160th Street P.O. Box 35906 Cleveland, Ohio 44135, U.S.A. <http://www.oatey.com>
Oatey Phone Number: (216) 267-7100 or (800) 321-9532
Emergency Phone Numbers: For Emergency First Aid call 1-877-740-5015. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1-703-527-3887.
Prepared By: Technical Department
Preparation Date: May 1, 2009

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENTS:</u>	<u>% wt/wt:</u>	<u>CAS NUMBER:</u>	<u>ACGIH TLV TWA:</u>	<u>OSHA PEL TWA:</u>
Petrolatum	60 - 70%	8009-03-8	5 mg/m3 (oil mist)	5 mg/m3 (oil mist)
Zinc Chloride	15 - 25%	7646-85-7	1 mg/m3 (fume) 2 mg/m3 STEL	1 mg/m3 (fume)
Ammonium Chloride	1 - 5%	12125-02-9	10 mg/m3 (fume) 20 mg/m3 STEL	None Established
Tin	4 - 8%	7440-31-5	2 mg/m3	2 mg/m3
Copper	0 - 1%	7440-50-8	0.2 mg/m3	0.1 mg/m3
Bismuth	0 - 1%	7440-69-9	None Established	None Established

SECTION 3 HAZARDS IDENTIFICATION
Emergency Overview:
Yellow paste with a slight odor. May cause burns to the eye and skin. Inhalation of fumes may cause respiratory irritation, metal fume fever, chills, nausea and vomiting. Swallowing may cause burns to the mouth or throat, vomiting, diarrhea and kidney or liver disorders. May be harmful if swallowed. Symptoms may be delayed.
OSHA Hazard Classification: Corrosive, target organ effects

SECTION 4 FIRST AID MEASURES
CALL 1-877-740-5015 or 1-303-623-5716 COLLECT
Skin: Remove contaminated clothing. Wash thoroughly with soap and water. Call a physician or poison control center if irritation persists.
Eyes: If material gets into eyes or if fumes cause irritation, immediately flush eyes with plenty of water until chemical is removed. If irritation persists, get medical attention immediately.
Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Keep victim quiet and warm. Call a poison control center or physician immediately.
Ingestion: **DO NOT INDUCE VOMITING.** Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

SECTION 5 FIRE FIGHTING MEASURES

Flashpoint / Method: 540 Degrees F (282 Degrees C)
Flammability: LEL = Not determined, UEL = Not determined
Extinguishing: Small Fires: Use dry chemical, CO2, water, or foam extinguisher
Media: Large Fires: Evacuate area and call Fire Department immediately
Special Fire Fighting: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored
Procedure:
Unusual Fire and Explosion: None known.
Hazards:
Hazardous: Hydrocarbons, hydrogen chloride, zinc fumes, tin fumes, copper
Decomposition: fumes, ammonia, smoke, carbon monoxide, carbon dioxide,
Products: nitrogen oxides, and bismuth fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill or Leak: Ventilate area. Stop leak if it can be done without risk. Personnel cleaning up the spill should wear appropriate personal protective equipment.
Procedures: Take up spill with sand, earth or other absorbent material and place into a clean, dry leak-proof container.

SECTION 7 HANDLING AND STORAGE

Handling: Do not get in eyes. Do not get on skin or clothing. Do not take internally. Avoid breathing vapors or fumes. Use only with adequate ventilation. Wash thoroughly after handling. Keep container closed when not in use. Handle with care. Keep out of reach of children.
Storage: Store in original, labeled container.
Other: Containers, even empty will retain residue and may be harmful.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Good general ventilation (equivalent to outdoors) should be adequate for normal use. For operations where the TLV may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.
Respiratory Protection: For operations where the TLV may be exceeded, a NIOSH approved particulate respirator or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.
Skin Protection: Wear rubber gloves.
Eye Protection: Safety glasses with sideshields or safety goggles.
Other: Eye wash and safety shower should be available.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 638 Degrees F (337 Degrees C)
Melting Point: Not determined
Vapor Pressure: Not determined
Vapor Density: (Air = 1) Greater than 1
Volatile Components: 1-4%
Solubility In Water: Negligible
pH: Not applicable
Specific Gravity: 1.1 @ 20 Degrees C
Evaporation Rate: Not applicable
Appearance: Green Paste
Odor: Very little odor
Will Dissolve In: Methylene Chloride
Material Is: Paste

SECTION 10 STABILITY AND REACTIVITY

Stability: Stable.
Conditions To Avoid: None.
Hazardous Decomposition Products: Hydrocarbons, hydrogen chloride, zinc fumes, tin fumes, copper fumes, ammonia, smoke, carbon monoxide, carbon dioxide, nitrogen oxides, and bismuth fumes.
Incompatibility/ Materials To Avoid: Strong oxidizing agents, potassium, cyanides and sulfides.
Hazardous Polymerization: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Inhalation: Fumes from heated product may be corrosive to mucous membranes and the respiratory system. Fumes may cause burning sensation, coughing, wheezing, shortness of breath, cyanosis, fever, chills, muscular pain, anemia, metallic taste in the mouth, headache, nausea, vomiting, sweating, diarrhea and pulmonary edema. Fumes may cause stannosis, a mild benign pneumoconiosis. Repeated inhalation of fumes may cause occupational asthma. Symptoms may be delayed.

Skin: Contact may cause irritation, ulcerations, burns or dermatitis. Symptoms may be delayed.

Eye: Vapors or fumes may cause redness, pain, blurred vision and corneal damage. Direct contact may cause burns and eye damage with possible blindness. Symptoms may be delayed.

Ingestion: May cause irritation or burns to the mouth and throat, nausea, vomiting or diarrhea. Death may occur from strictures of the esophagus and pylorus. Symptoms may be delayed.

Toxicity Data:

Petrolatum:	No data available
Zinc Chloride:	Oral rat LD50: 350 mg/kg
Ammonium Chloride:	Oral rat LD50: 1,650 mg/kg
Bismuth:	Oral rat LD50: 5 mg/kg
Tin:	No data available
Copper:	No data available

Sensitization: None of the components are known to cause sensitization.

Carcinogenicity: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA.

Mutagenicity: None of the components have been found to be mutagenic.

Reproductive Toxicity: None of the components are known to cause adverse reproductive effects.

Medical Conditions Aggravated By Exposure: Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to this product.

SECTION 12 ECOLOGICAL INFORMATION

No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of in accordance with federal, state, and local regulations. It is the responsibility of the end-user to determine at the time of disposal of the product.

RCRA Hazardous Waste Number: None
EPA Hazardous Waste ID Number: None
EPA Hazard Waste Class: None

SECTION 14 TRANSPORT INFORMATION

DOT

Proper Shipping Name: Not applicable
Hazard Class/Packing Group: None
UN/NA Number: None
Hazard Labels: None

IMDG

Proper Shipping Name: Not applicable
Hazard Class/Packing Group: None
UN Number: None
Label: None

2004 North American Emergency Response Guidebook Number: None

SECTION 15 REGULATORY INFORMATION

Hazard Category for Section 311/312: Acute Health, Chronic Health

Section 302 Extremely Hazardous Substances (TPQ): This product does not contain chemicals regulated under SARA Section 302.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

<u>Chemical</u>	<u>CAS #</u>	<u>% wt</u>
Zinc Chloride	7646-85-7	15-25%

CERCLA 103 Reportable Quantity:

Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Zinc Chloride (25% max) of 1,000 lbs, is 4,000 lbs.

<u>Chemical</u>	<u>CAS #</u>	<u>RQ, lbs.</u>
Zinc Chloride	7646-85-7	1,000
Ammonium Chloride	12125-02-6	5,000

California Proposition 65:

Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

TSCA Inventory:

This product does not contain chemicals regulated under California Proposition 65.
All of the components of this product are listed on the TSCA inventory.

Canadian WHMIS Classification:

Class E; Class D, Division 2, Subdivision B
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

SECTION 16 OTHER INFORMATION

NFPA and HMIS:

NFPA Hazard Signal: Health: 3 Flammability: 1 Reactivity: 0 Special: None

HMIS Hazard Signal: Health: 3* Flammability: 1 Reactivity: 0 PPE: B

Disclaimer:

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, Oatey cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.



MATERIAL SAFETY DATA SHEET

MSDS Number: 1402E

Section 1 PRODUCT AND COMPANY IDENTIFICATION

Trade Name: OATEY PURPLE or CLEAR PRIMER NSF LISTED
Product Nos.: Purple - 30755, 30756, 30757, 30758, 30759, 30927 Clear - 30749, 30750, 30751, 30752, 30753, 30754, 31652, 31653
Product Use: Primer for PVC and CPVC Plastic Pipe
Formula: See section 2
Synonyms: Plastic Pipe Primer
Firm Name & Address: Oatey Company 4700 West 160th Street, Cleveland, Ohio 44135
Firm Phone No: (216) 267-7100
Emergency Phone Nos.: For Emergency First Aid call 1-877-740-5015. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1-703-527-3887.
Prepared by: Technical Department
Preparation Date: 11/01/2009

Section 2 HAZARDS IDENTIFICATION

Emergency Overview: Purple or Clear liquid with an ether-like odor. Extremely flammable liquid and vapor. Vapors may cause flash fire. May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects. Swallowing may cause irritation, nausea, vomiting, diarrhea and kidney or liver disorders. Aspiration hazard. May be fatal if swallowed. Symptoms may be delayed.

Section 3 COMPOSITION/INFORMATION ON INGREDIENTS

Table with 6 columns: INGREDIENTS, %wt/wt, CAS NUMBER, ACGIH TLV TWA, OSHA PEL TWA, OTHER. Rows include Tetrahydrofuran, Methyl Ethyl Ketone, Acetone, and Cyclohexanone.

OSHA Hazard Classification: Flammable, irritant, organ effects

Section 4 FIRST AID MEASURES

Skin: Remove contaminated clothing immediately. Wash all exposed areas with soap and water. Get medical attention if irritation develops. Remove dried cement with hand cleaner or baby oil.
Eyes: If material gets into eyes or if fumes cause irritation, immediately flush eyes with plenty of water until chemical is removed. If irritation persists, get medical attention immediately.

Inhalation: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.

Ingestion: **DO NOT INDUCE VOMITING.** Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

Section 5 FIRE FIGHTING MEASURES

Flashpoint / Method: 14 - 23 Degrees F. (-10 to -5 Degrees C) / CCCFP

Flammability: LEL = 1.8 % Volume, UEL = 11.8 % Volume

Extinguishing Media: Use dry chemical, CO2, or foam to extinguish fire. Cool fire exposed container with water. Water may be ineffective as an extinguishing agent.

Special Fire Fighting Procedure: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored

Unusual Fire And Explosion Hazards: Extremely flammable liquid. Keep away from heat and all sources of ignition including sparks, flames, lighted cigarettes and pilot lights. Containers may rupture or explode in the heat of a fire. Vapors are heavier than air and may travel to a remote ignition source and flash back. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

Hazardous Decomposition Products: Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.

Section 6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Remove all sources of ignition and ventilate area. Stop leak if it can be done without risk. Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high. Soak up spill with an inert absorbent such as sand, earth or other non-combusting material. Put absorbent material in covered, labeled metal containers. Prevent liquid from entering watercourses, sewers and natural waterways. Report releases to authorities as required. See Section 13 for disposal information.

Section 7 HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use with adequate ventilation (equivalent to outdoors). Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

Storage: Store in a cool, dry, well-ventilated area away from incompatible materials. Keep containers closed when not in use.

Other: "Empty" containers retain product residue and can be hazardous. Follow all MSDS precautions in handling empty containers. Do not cut or weld on or near empty or full containers.

Section 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Open doors & windows. Provide ventilation capable of maintaining emissions at the point of use below recommended exposure limits. If used in enclosed area, use exhaust fans. Exhaust fans should be explosion-proof or set up in a way that flammable concentrations of solvent vapors are not exposed to electrical fixtures or hot surfaces.

Respiratory Protection: For operations where the exposure limit may be exceeded, a NIOSH approved organic vapor respirator or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration, select in accordance

with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Skin Protection: Rubber gloves are suitable for normal use of the product. For long exposures chemical resistant gloves may be required such as 4H(tm) or Silver Shield(tm) to avoid prolonged skin contact.

Eye Protection: Safety glasses with side shields or safety goggles.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 151 Degrees F / 66 Degrees C
Melting Point: Not applicable
Vapor Pressure: 145 mmHg @ 20 Degrees C
Vapor Density: (Air = 1) 2.5
Volatile Components: 99.96%
Solubility In Water: Negligible
pH: Not applicable
Specific Gravity: 0.84 +/- 0.02 @ 20 Degrees C
Evaporation Rate: (BUAC = 1) = 5.5 - 8.0
Appearance: Purple or Clear Liquid
Odor: Ether-Like
Will Dissolve In: Tetrahydrofuran
Material Is: Liquid

Section 10 STABILITY AND REACTIVITY

Stability: Stable.
Conditions To Avoid: Avoid heat, sparks, flames and other sources of ignition.
Hazardous Decomposition Products: Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.
Incompatibility/ Materials To Avoid: Oxidizing agents, alkalis, amines, ammonia, acids, chlorine compounds, chlorinated inorganics (potassium, calcium and sodium hypochlorite) and hydrogen peroxides. May attack plastic, resins and rubber.
Hazardous Polymerization: Will not occur.

Section 11 TOXICOLOGICAL INFORMATION

Inhalation: Vapors or mists may cause mucous membrane and respiratory irritation, coughing, headache, dizziness, dullness, nausea, shortness of breath and vomiting. High concentrations may cause central nervous system depression, narcosis and unconsciousness. May cause kidney, liver and lung damage.

Skin: May cause irritation with redness, itching and pain. Methyl ethyl ketone and cyclohexanone may be absorbed through the skin causing effects similar to those listed under inhalation.

Eye: Vapors may cause irritation. Direct contact may cause irritation with redness, stinging and tearing of the eyes. May cause eye damage.

Ingestion: Swallowing may cause abdominal pain, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting can cause chemical pneumonia and lung damage. May cause kidney and liver damage.

Chronic Toxicity: Prolonged or repeated overexposure cause dermatitis and damage to the kidney, liver, lungs and central nervous system.

Toxicity Data:

Acetone:	Oral rat LD50: 5,800 mg/kg
	Inhalation rat LC50: 50,100 mg/m ³ /8 hours
Cyclohexanone:	Oral rat LD50: 1,620 mg/kg
	Inhalation rat LC50: 8,000 ppm/4 hours
	Skin rabbit LD50: 1 mL/kg

Tetrahydrofuran: Oral rat LD50: 1,650 mg/kg
 Inhalation rat LC50: 21,000 ppm/3 hours
 Methyl Ethyl Ketone: Oral rat LD50: 2,737 mg/kg
 Inhalation rat LC50: 23,500 mg/m3/8 hours
 Skin rabbit LD50: 6,480 mg/kg

Sensitization: None of the components are known to cause sensitization.
 Carcinogenicity: None of the components are listed as a carcinogen or suspect carcinogen by NTP, IARC or OSHA. The National Toxicology Program has reported that exposure of mice and rats to tetrahydrofuran (THF) vapor levels up to 1800 ppm 6 hr/day, 5 days/week for their lifetime caused an increased incidence of kidney tumors in male rats and liver tumors in female mice. The significance of these findings for human health is unclear at this time, and may be related to "species specific" effects. Elevated incidences of tumors in humans have not been reported for THF. ACGIH has classified cyclohexanone (CYH) and tetrahydrofuran as "A3," Confirmed Animal Carcinogens with Unknown Relevance to Humans.
 Mutagenicity: Cyclohexanone has been positive in bacterial and mammalian assays. Acetone, methyl ethyl ketone and tetrahydrofuran are generally thought not to be mutagenic.
 Reproductive Toxicity: Methyl ethyl ketone and cyclohexanone have been shown to cause embryofetal toxicity and birth defects in laboratory animals. Acetone and tetrahydrofuran has been found to cause adverse developmental effects only when exposure levels cause other toxic effects to the mother.
 Medical Conditions Aggravated By Exposure: Persons with pre-existing skin, lung, kidney or liver disorders may be at increased risk from exposure to this product.

Section 12 ECOLOGICAL INFORMATION

This product is not expected to be toxic to aquatic organisms.
 Cyclohexanone: 96 hour LC50 values for fish is over 100 mg/l.
 Tetrahydrofuran: 96 hour LC50 fathead minnow: 2160 mg/L.
 Acetone: 96 hour LC50 for fish is greater than 100 mg/L.
 Methyl Ethyl Ketone: 96 hour LC50 for fish is greater than 100 mg/L.
 VOC Information: This product emits VOC's (volatile organic compounds) in its use. Make sure that use of this product complies with local VOC emission regulations, where they exist.
 VOC Level: Maximum 550 g/L per SCAQMD Test Method 316A.

Section 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose in accordance with current local, state and federal regulations.
 RCRA Hazardous Waste Number: U002, U057, U159, U213
 EPA Hazardous Waste ID Number: D001, D035, F003, F0005
 EPA Hazard Waste Number: Ignitable Waste. Toxic Waste (Methyl Ethyl Ketone content)

Section 14 TRANSPORT INFORMATION

DOT	<u>Less than 1 Liter (0.3 gal)</u>	<u>Greater than 1 Liter (0.3 gal)</u>
UN/NA Number:	None	UN1993
Proper Shipping Name:	Consumer Commodity	Flammable Liquid, NOS (Methyl Ethyl Ketone, Acetone)
Hazard Class:	ORM-D	3

Packing Group:	None	PGII
Hazard Labels:	None	Flammable Liquid
IMDG		
UN Number:	UN1993	UN1993
Proper Shipping Name:	Flammable Liquid, NOS (Limited Quantity)	Flammable Liquid, NOS (Methyl Ethyl Ketone, Acetone)
Hazard Class:	3	3
Packing Group:	II	II
Label:	None (Limited Quantities are expected from labeling)	Class 3 (Flammable Liquid)
Flashpoint (deg C)	-10 to -5 Degrees C	-10 to -5 Degrees C

2008 North American Emergency Response Guidebook Number: 127

Section 15 REGULATORY INFORMATION

Hazard Category for Acute Health, Chronic Health, Flammable
Section 311/312:

Section 302 This product does not contain chemicals regulated under SARA Section 302.
Extremely Hazardous
Substances (TPQ):

Section 313 Toxic This product does not contain chemicals subject to SARA Title III Section
Chemicals: 313 Reporting requirements.
CERCLA 103 Spills of this product over the RQ (reportable quantity) must be reported
Reportable to the National Response Center. The RQ for the product, based on the RQ
Quantity: for Tetrahydrofuran (30% maximum) of 1,000 lbs, is 3,333 lbs.
Many states have more stringent release reporting requirements. Report
spills required under federal, state and local regulations.

California This product does not contain any chemicals subject to California
Proposition 65: Proposition 65 regulations.

TSCA Inventory All of the components of this product are listed on the TSCA inventory.
Canadian WHIMS Class B, Division 2; Class D, Division 2, Subdivision B; Class D,
Classification: Division 2, Subdivision A. This product has been classified in accordance
with the hazard criteria of the Controlled Products Regulations (CPR) and
the MSDS contains all the information required by the CPR.

Section 16 OTHER INFORMATION

NFPA and HMIS:
NFPA Hazard Signal: Health: 2 Flammability: 3 Reactivity: 1 Special: None
HMIS Hazard Signal: Health: 2* Flammability: 3 Reactivity: 1 PPE: G

Disclaimer:

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources, and expressly does not make warranties, nor assumes any liability for its use.

Template: tmpl-us-e1