

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

SECTION 1. IDENTIFICATION

Product name : Genetron® 410A

Number : 000000009881

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 800-522-8001
+1-973-455-6300
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : weak

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Prevention:**
Use personal protective equipment as required.

Storage:
Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise classified

: May cause eye and skin irritation.
May cause frostbite.
May cause cardiac arrhythmia.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

: Difluoromethane and Pentafluoroethane

Formula

: CH₂F₂ and CHF₂CF₃

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
Pentafluoroethane	354-33-6	50.00 %
Difluoromethane	75-10-5	50.00 %

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.
- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Indication of immediate medical attention and special treatment needed, if necessary : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : The product is not flammable.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting : This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Fire may cause evolution of:
Halogenated compounds
Hydrogen fluoride
Carbon oxides
Carbonyl halides
- Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Methods and materials for containment and cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.
Wear personal protective equipment.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Storage

Conditions for safe storage, including any incompatibilities : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.
Store away from incompatible substances.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.
Avoid contact with skin, eyes and clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.
Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection : Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
When using do not eat, drink or smoke.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.
Do not breathe vapour.
Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Difluoromethane	75-10-5	TWA : Time weighted average	2,200 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide

Difluoromethane	75-10-5	TWA : Time weighted average	(1,000 ppm)	1994	Honeywell:Limit established by Honeywell International Inc.
-----------------	---------	--------------------------------	-------------	------	---

Pentafluoroethane	354-33-6	TWA : Time weighted average	4,900 mg/m3 (1,000 ppm)	2007	WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide
-------------------	----------	--------------------------------	----------------------------	------	--

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Pentafluoroethane	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
-------------------	----------	-----------------------------------	-------------	--	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquefied gas
Color	: colourless
Odor	: weak
pH	: Note: neutral
Freezing point	: Note: not determined
Boiling point/boiling range	: -48.5 °C
Flash point	: Note: Not applicable
Evaporation rate	: > 1 Method: Compared to CCl4.
lower flammability limit	: Note: None
upper flammability limit	: Note: None
Vapor pressure	: 14,844 hPa at 21.1 °C(70.0 °F) 33,798 hPa at 54.4 °C(129.9 °F)

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Vapor density : 3 Note: (Air = 1.0)

Density : 1.08 g/cm³ at 21.1 °C

Water solubility : Note: no data available

Partition coefficient: n-octanol/water : log Pow: 1.48
Test substance: Ethane, pentafluoro- (HFC-125)
log Pow: 0.21
Test substance: Difluoromethane (HFC-32)

Ignition temperature : > 750 °C

Decomposition temperature : > 250 °C

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous polymerisation does not occur.

Conditions to avoid : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Decomposes under high temperature.
Some risk may be expected of corrosive and toxic decomposition products.
Can form a combustible mixture with air at pressures above atmospheric pressure.
Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials : Finely divided aluminium

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Potassium
Calcium
Powdered metals
Aluminium
Magnesium
Zinc

Hazardous decomposition products : Halogenated compounds
Hydrogen fluoride
Carbonyl halides
Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity
Pentafluoroethane : > 769000 ppm
Exposure time: 4 h
Species: Rat

Difluoromethane : LC50: > 520000 ppm
Exposure time: 4 h
Species: Rat

Sensitisation
Pentafluoroethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
75 000 ppm
Lowest observed effect level
100 000 ppm

Difluoromethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
>350 000 ppm

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Repeated dose toxicity

Pentafluoroethane

: Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOEL: 50000 ppm
Subchronic toxicity

Difluoromethane

: Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 50000 ppm
Subchronic toxicity

Genotoxicity in vitro

Pentafluoroethane

: Test Method: Ames test
Result: negative

Difluoromethane

: Test Method: Ames test
Result: negative

: Cell type: Human lymphocytes
Result: negative

: Cell type: Chinese Hamster Ovary Cells
Result: negative

: Cell type: Human lymphocytes
Result: negative
Method: Mutagenicity (in vitro mammalian cytogenetic test)

: Test Method: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo

Difluoromethane

: Species: Mouse
Cell type: Bone marrow
Method: Mutagenicity (micronucleus test)
Result: negative

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Teratogenicity

Pentafluoroethane

: Species: Rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: Rat

Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Difluoromethane

: Species: Rat
Dose: NOEL - 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Species: Rabbit

Dose: NOEL - 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.

Further information

: Acute toxicity Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. May cause cardiac arrhythmia.

SECTION 12. ECOLOGICAL INFORMATION

Biodegradability

Pentafluoroethane

: Result: Not readily biodegradable.
Value: 5 %
Method: OECD 301 D

Difluoromethane

: Note: Minimal

Further information on ecologyAdditional ecological
information

: This product is subject to U.S. Environmental Protection
Agency Clean Air Act Regulations at 40 CFR Part 82.

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

- Disposal methods : Observe all Federal, State, and Local Environmental regulations.
- Note : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

- DOT**
- | | |
|----------------------|---|
| UN/ID No. | : UN 3163 |
| Proper shipping name | : LIQUEFIED GAS, N.O.S.
(Pentafluoroethane, Difluoromethane) |
| Class | : 2.2 |
| Packing group | |
| Hazard Labels | : 2.2 |
- IATA**
- | | |
|--|---|
| UN/ID No. | : UN 3163 |
| Description of the goods | : LIQUEFIED GAS, N.O.S.
(Pentafluoroethane, Difluoromethane) |
| Class | : 2.2 |
| Hazard Labels | : 2.2 |
| Packing instruction (cargo aircraft) | : 200 |
| Packing instruction (passenger aircraft) | : 200 |
- IMDG**
- | | |
|--------------------------|--|
| UN/ID No. | : UN 3163 |
| Description of the goods | : LIQUEFIED GAS, N.O.S.
(PENTAFLUOROETHANE,
DIFLUOROMETHANE) |
| Class | : 2.2 |

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

000000009881


Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Acute Health Hazard
Sudden Release of Pressure Hazard

California Prop. 65 :  **WARNING:** This product can expose you to chemicals, listed below, known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Dichloromethane 75-09-2

Massachusetts RTK : Dichloromethane 75-09-2

New Jersey RTK : Difluoromethane 75-10-5

Pennsylvania RTK : Difluoromethane 75-10-5

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

000000009881

Version 3.0

Revision Date 08/08/2018

Print Date 09/03/2020

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 04/18/2014

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group